HOUSTON, TEXAS

HI-ILS Y or LOC Y RWY 35L

LOC I-EFD	APCH CRS	Rwy Idg / TDZE / Arpt Elev
111.1	354°	9001 / 28 / 33

[USAF] ELLINGTON (KEFD)

DME required. RADAR required for procedure entry.
▼ * When ALS inop, increase CAT CDE RVR to 60.
** Circling not authorized W of rwy 17L-35R

MALSF

MISSED APPROACH: Climb to 500 then climbing right turn to 3100 via EFD TACAN R-136 to WATFO/EFD 16 DME and hold.

ATIS	HOUSTON APP CON	TOWER	GND CON
135.575 269.9	134.45 284.0	126.05 253.5	121.6 275.8

EFD TACAN	N29°36.36′ W95°09.58′
CANDI	N29°39.24′ W95°18.17′
DROPP	N29°13.63′ W95°32.07′
WATFO	N29°23.90′ W94°58.07′

IAF ELLINGTON Chan 31 EFD

LOCALIZER 111.1 I-EFD

(IAF) CANDI EFD 8 16,000

JUVUM EFD 2.5 14,000 12,000

MARZY RADAR EFD 7

DME from EFD TACAN, simultaneous reception of I-EFD and EFD DME required.

WATFO EFD 16

TRINITY 114.75 MHF Chan 94(Y)

(IF) PAHSU RADAR EFD 15

EDF EFD 18

EDEDY EFD 18

KOREJ EFD 18

(IAF) DROPP EFD 30 16,000

ANRUY EFD 30 15,000

OKUME EFD 30

M.S.A EFD 2.5 NM
150°–330°
3100
1800

EMERG SAFE ALT 100 NM 16,000



CATEGORY	C	D	E
S-ILS 35L	228/40	200	(200-¾)
S-LOC 35L *	440/50	412	(500-1)
C CIRCLING **	580-1½ 547 (600-1½)	640-2 607 (700-2)	700-2¼ 667 (700-2¼)

ELEV 33 D TDZE 28



HOUSTON, TEXAS 29°36′N-95°10′W ELLINGTON (KEFD)

Amdt 4A 15AUG19

HI-ILS Y or LOC Y RWY 35L

SC-5, 18 APR 2024 to 16 MAY 2024