EVVAN THREE DEPARTURE (RNAV)

(EVVAN3.EVVAN) 25JUN15

NASHVILLE, TENNESSEE
NASHVILLE INTL (BNA)

D-ATIS 135.1
CLNC DEL 126.05
CPDLC
GND CON
121.9 348.6
NASHVILLE TOWER
118.6 257.8
NASHVILLE DEP CON
118.4 360.7

TOP ALTITUDE: 4000

TAKEOFF MINIMUMS:
Rwys 2C, 2L, 2R, 13, 20C, 20L, 20R, 31: Standard with minimum climb of 500' per NM to 1100.



NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.
NOTE: Radar required.
NOTE: For Turbojet aircraft only.
NOTE: Transponder code will be issued via PDC or Nashville clearance delivery.
NOTE: If unable to accept climb rates, advise ATC on initial contact.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence....
TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence....
TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence....
TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence....

....expect radar vectors to CHPPY, then on track 115° to EVVAN. Maintain 4000, expect clearance to filed altitude within five (5) minutes after departure.

NOTE: Chart not to scale.

(EVVAN3.EVVAN) 18088 AL-282 (FAA)
EVVAN THREE DEPARTURE (RNAV)
NASHVILLE INTL (BNA)
NASHVILLE, TENNESSEE