# RNAV (RNP) Z RWY 31

NASHVILLE INTL (BNA)

| APP CRS | Rwy Idg | 9487 |
|---|---|---|
| 316° | TDZE | 578 |
| | Apt Elev | 599 |

For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). GPS required.

MISSED APPROACH: Climb to 3100 on track 316° to JARAS and hold.

| D-ATIS | NASHVILLE APP CON | NASHVILLE TOWER | GND CON | CLNC DEL | CPDLC |
|---|---|---|---|---|---|
| 135.1 | 118.4 360.7 | 118.6 257.8 | 121.9 348.6 | 126.05 | |




| ELEV 599 | D | TDZE 578 |
|---|---|---|




HIRL all Rwys
TDZ/CL Rwys 2L and 2R
REIL Rwys 13, 20C, and 31

| 3100 | tr 316° | JARAS | See planview for multiple IF locations. |
|---|---|---|---|




| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| RNP 0.25 DA | 1025-1½ 447 (500-1½) | | | |
| RNP 0.30 DA | 1099-1¾ 521 (600-1¾) | | | |

AUTHORIZATION REQUIRED



SE-1, 18 APR 2024 to 16 MAY 2024
SE-1, 18 APR 2024 to 16 MAY 2024