ILS or LOC RWY 26

PHOENIX SKY HARBOR INTL (PHX)

LOC/DME I-CWJ	APP CRS	Rwy Idg 11489
111.75	258°	TDZE 1135
Chan 54 (Y)		Apt Elev 1135

DME or RADAR required.

Simultaneous approach authorized.

MISSED APPROACH: Climb to 2500 then climbing right turn to 5000 on heading 030° and PXR VORTAC R-336 to AVENT/PXR 15.9 DME and hold.

D-ATIS	PHOENIX APP CON	PHOENIX TOWER	GND CON	CLNC DEL	CPDLC
127.575	128.65 353.9	118.7 278.8 (Rwy 8-26) 120.9 254.3 (Rwy 7L-25R, 7R-25L)	119.75 269.2 (N) 132.55 269.2 (S)	118.1 269.2	



ELEV 1135 | D | TDZE 1135



HIRL Rwys 8-26, 7L-25R and 7R-25L
REIL Rwy 26

FAF to MAP 5.7 NM

Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54



CATEGORY	A	B	C	D
S-ILS 26	1385-¾ 250 (300-¾)			
S-LOC 26	1580-1 445 (500-1)		1580-1⅜ 445 (500-⅜)	
C CIRCLING	1740-1 605 (700-1)		2040-2¾ 905 (1000-2¾)	2560-3 1425 (1500-3)

SW-4, 18 APR 2024 to 16 MAY 2024
SW-4, 18 APR 2024 to 16 MAY 2024