

RNAV (GPS) Y RWY 7L
PHOENIX SKY HARBOR INTL (PHX)

PHOENIX SKY HARBOR INTL (PHX)

MISSED APPROACH: Climb to 5000 direct UXCUN and via 111° track to IWA VORTAC and hold.

⚠ For inop ALS, increase visibility LPV all Cats to RVR 4500, LNAV/VNAV all Cats to RVR 6000, LNAV Cats C/D to 1% SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations.

BUCKEYE
BKK

5000
079°
(25.1)

4 NM

258°

078°

4000 NoPT
090° (3.3)

3000
078°
(6.1)

(IAF)
AVONA

(IF/IAF)
UPNIW

1535

(FAF)
YECXY

PETRS
2.1 NM to
RW07L

1602

1330

1475

1573

1472

1276±

1502

PHOENIX
PXR

111°

UXCUN

2608

2704

1760

3068

2555

3650

4512

4160

MSA RW07L 25 NM

6100

WILLIE
IWA

360°

180°

5 NM

ELEV 1135

TDZE 1116

SW-4, 18 APR 2024 to 16 MAY 2024

SW-4. 18 APR 2024 to 16 MAY 2024

