

WAAS

CH **73005**

W12A

APP CRS

126°

Rwy Idg

8279

TDZE

3963

Apt Elev

3967

RNAV (GPS) RWY 12

WESTERN NEBRASKA RGNL/WILLIAM B HEILIG FLD (BTF)

⚠

When local altimeter setting not received, use Alliance altimeter setting and increase all DAs 91 feet and all MDAs 100 feet; increase LPV, LNAV/VNAV, LNAV Cat A/B and Circling Cat B visibilities ¼ mile; increase LNAV and Circling Cat C/D visibilities ½ mile. For inoperative MALSR, when using Alliance altimeter setting, increase LPV all Cats visibility to 1¼, and LNAV Cat A visibility to 1. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 41°C (105°F). Baro-VNAV NA when using Alliance altimeter setting. VDP NA when using Alliance altimeter setting. DME/DME RNP-0.3 NA.

MALSR

MISSED APPROACH:
Climb to 6700 direct HAKAB and hold.

ASOS 121.025	DENVER CENTER 127.95 338.2	UNICOM 123.0 (CTAF) 1
------------------------	--------------------------------------	---------------------------------

Procedure NA for arrivals at ALBIN V81 southwest bound and arrivals at SPONS V81-V169 northbound.

ALBIN V81 SW bound, SPONS V81-V169 NB bound

ELEV 3967

D

TDZE 3963

HIRL Rwy 12-30 1
MRL Rwy 5-23 1

7 NM Holding Pattern				LEDSE	CAPGA	RW12		
6900				305°	125°	126°		
GP 3.00°				5700				
TCH 57				6.1 NM				
				3.1 NM				
				2.1 NM				
CATEGORY	A	B	C	D				
LPV DA	4213-½ 250 (300-½)							
LNAV/VNAV DA	4340-¾ 377 (400-¾)							
LNAV MDA	4700-½ 737 (800-½)		4700-1½ 737 (800-1½)		4700-1¾ 737 (800-1¾)			
CIRCLING	4700-1 733 (800-1)		4700-2 733 (800-2)		4740-2½ 773 (800-2½)			

SCOTTSBLUFF, NEBRASKA

Amtd 1A 30JAN20

WESTERN NEBRASKA RGNL/WILLIAM B HEILIG FLD (BTF)

41°52'N-103°36' W

RNAV (GPS) RWY 12