RNAV (GPS) RWY 15

CRAIG FLD (SEM)

WAAS	APP CRS	Rwy Idg	8014
CH 69435	149°	TDZE	166
W15A		Apt Elev	166

Baro-VNAV NA when using Montgomery altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Montgomery altimeter setting. When local altimeter setting not received, use Montgomery altimeter setting and increase all DA 78 feet, all MDA 80 feet, LPV all Cats visibility ⅜ mile, LNAV/VNAV all Cats visibility and LNAV Cats C and D visibility ¼ mile, Circling Cat C visibility ½ mile and Cat D visibility ¼ mile.

MISSED APPROACH: Climb to 3100 direct CADIP and hold.

AWOS-3PT	MONTGOMERY APP CON ★	CRAIG TOWER★	GND CON	UNICOM
119.15	124.0 363.025	120.85	121.675	122.7 (CTAF) L





HIRL Rwy 15-33 L



CATEGORY	A	B	C	D
LPV DA	416-¾ 250 (300-¾)			
LNAV/ VNAV DA	569-1⅜ 403 (500-1⅜)			
LNAV MDA	560-1 394 (400-1)		560-1⅛ 394 (400-1⅛)	
C CIRCLING	660-1 494 (500-1)	760-1 594 (600-1)	760-1½ 594 (600-1½)	1040-2¾ 874 (900-2¾)

SE-4, 18 APR 2024 to 16 MAY 2024
SE-4, 18 APR 2024 to 16 MAY 2024