| WAAS CH 57911 W13A | APP CRS 133° | Rwy Idg 9002 TDZE 1095 Apt Elev 1098 |
|---|---|---|

# RNAV (GPS) RWY 13

## SIOUX GATEWAY/BRIG GENERAL BUD DAY FLD (SUX)

RNP APCH-GPS.

Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. For inop ALS, increase LNAV/VNAV Cat E visibility to 1⅝ SM and LNAV Cat E visibility to 1½ SM.

MALS

MISSED APPROACH: Climb to 3900 direct WAVUK and hold.

| ATIS | SIOUX CITY APP CON ★ | SIOUX CITY TOWER ★ | GND CON | UNICOM |
|---|---|---|---|---|
| 119.45 270.8 | 124.6 307.0 | 118.7 (CTAF) L 254.3 | 121.9 348.6 | 122.95 |




ELEV 1098 D TDZE 1095




REIL Rwy 18 L
HIRL Rwy 13-31 L
MIRL Rwy 18-36 L




| CATEGORY | A | B | C | D | E |
|---|---|---|---|---|---|
| LPV DA | 1295/40 200 (200-¾) | | | | |
| LNAV/VNAV DA | 1582/60 487 (500-1¼) | | | | |
| LNAV MDA | 1620/40 525 (600-¾) | | 1620-1¼ 525 (600-1¼) | | |
| C CIRCLING | 1640-1 542 (600-1) | 1700-1 602 (700-1) | 1700-1¾ 602 (700-1¾) | 1860-2½ 762 (800-2½) | 2000-3 902 (1000-3) |



NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024