

TACAN Y RWY 22R

TACAN SSC Chan 38	APCH CRS 222°	22R	22L
		Rwy Ldg	10,014 8014
		TDZE	240 235
		Arprt Elev	241 241

AL-409 [USAF]

SHAW AFB (KSSC)

▼ * When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1½ miles.
** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1¾ miles.

ALSF-1

A1

MISSED APPROACH: Climbing to 2000, intercept SSC TACAN R-223 to PINIE and hold.

ATIS ★ 132.125 270.1	SHAW APP CON 125.4 318.1	SHAW TOWER ★ 126.65 254.25	GND CON 126.1 275.8	CLNC DEL 126.1 275.8
-------------------------	-----------------------------	-------------------------------	------------------------	-------------------------

Sidestep Rwy 22L: Terrain 239' MSL, 200' prior to threshold, 200' right of course. When VGSI inop, sidestep procedure NA at night.

CAUTION: When Rwy 4L, 22L VGSI inop, circling to Rwy 4L, 22L NA at night. Terrain 239' MSL, 200' prior to threshold, 200' left of centerline.

USAF Only: When Rwy 22L VGSI inop, sidestep or circling to Rwy 22L authorized at night with MAJCOM A3 approval.

1573
▲

SSC 18

SSC 11

FASNO SSC 4.9

PINIE SSC 11

R-6002

SHAW Chan 38 SSC

RADAR required when R-6002 active.

1340
▲

EMERG SAFE ALT 100 NM 3800

2000
SSC R-223

PINIE SSC 11

TACAN

REBIE 1

FASNO 4.9

GABLE R-042 11

222° to SSC TACAN

222°

2000

2.96° TCH 51

CATEGORY	A	B	C	D	E
S-22R*	760/24 520 (600-½)		760/55 520 (600-1)		
SIDESTEP ** 22L	760/50 505 (600-1)		760/55 505 (600-1)		
CIRCLING	820-1 579 (600-1)	880-1 639 (700-1)	1000-2¼ 759 (800-2¼)	1000-2½ 759 (800-2½)	1000-2¾ 759 (800-2¾)

222° to SSC TACAN

519
▲

502
★

450
▲

392
▲

392
▲

340
▲

268
▲

HIRL all Rwy

TACAN Y RWY 22R

SE-2, 18 APR 2024 to 16 MAY 2024

SE-2, 18 APR 2024 to 16 MAY 2024