WAAS	APP CRS	Rwy Idg	7105
CH 78205	174°	TDZE	2878
W17A		Apt Elev	2885

RNAV (GPS) RWY 17
LIBERAL MID-AMERICA RGNL (LBL)

RNP APCH - GPS.

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Circling NA east of Rwy 17-35. When local altimeter setting not received, use Guymon altimeter setting and increase LPV DA 3240 feet; increase LNAV/VNAV DA to 3432 feet and all visibilities ¼ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM. VDP NA when using Guymon Muni altimeter setting. Baro-VNAV NA when using Guymon Muni altimeter setting.

MISSED APPROACH: Climb to 4500 direct OMVUE and hold.

AWOS-3PT	KANSAS CITY CENTER	UNICOM
118.375	134.0 257.625	122.8 (CTAF) L



MISSED APCH FIX



CATEGORY	A	B	C	D
LPV DA	3128-1 250 (300-1)			
LNAV/VNAV DA	3320-1⅜ 442 (500-1⅜)			
LNAV MDA	3260-1 382 (400-1)		3260-1⅛ 382 (400-1⅛)	
C CIRCLING	3320-1 435 (500-1)	3360-1 475 (500-1)	3640-2¼ 755 (800-2¼)	3640-2½ 755 (800-2½)

ELEV 2885 D TDZE 2878



REIL Rwys 4, 17 and 22 L
MIRL Rwy 4-22 L
HIRL Rwy 17-35 L

NC-2, 18 APR 2024 to 16 MAY 2024
NC-2, 18 APR 2024 to 16 MAY 2024