RNAV (GPS) RWY 35

LIBERAL MID-AMERICA RGNL (LBL)

WAAS	APP CRS	Rwy Idg	7105
CH 63005	354°	TDZE	2875
W35A		Apt Elev	2885

RNP APCH - GPS.

T A Baro-VNAV NA when using Guymon Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Circling NA east of Rwy 17-35. VDP NA when using Guymon Muni altimeter setting. When local altimeter setting not received, use Guymon altimeter setting and increase LPV DA to 3187 feet; increase LNAV/VNAV DA to 3237 feet and all visibilities ⅛ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ⅜ SM, and Circling visibility Cat D ¼ SM.

MALSR

MISSED APPROACH: Climb to 4600 direct ZAVEK and hold.

AWOS-3PT	KANSAS CITY CENTER	UNICOM
118.375	134.0 257.625	122.8 (CTAF) L



ELEV 2885 D TDZE 2875

REIL Rwys 4, 17 and 22 L

MIRL Rwy 4-22 L

HIRL Rwy 17-35 L





CATEGORY		A	B	C	D
LPV	DA	3075-½	200 (200-½)		
LNAV/VNAV	DA	3125-½	250 (300-½)		
LNAV MDA		3200-½	325 (400-½)		
C CIRCLING		3260-1 375 (400-1)	3340-1 455 (500-1)	3340-1½ 455 (500-1½)	3460-2 575 (600-2)

NC-2, 18 APR 2024 to 16 MAY 2024
NC-2, 18 APR 2024 to 16 MAY 2024