RNAV (GPS) RWY 5

BOCA RATON (BCT)

WAAS CH 82101 W05A	APP CRS 049°	Rwy Idg 5580 TDZE 12 Apt Elev 13

RNP APCH-GPS.

T A Baro-VNAV NA when using Palm Beach Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Palm Beach Intl altimeter setting: increase LPV DA to 326 feet; increase LNAV/VNAV DA to 501 feet; increase all MDAs 60 feet and visibility LNAV Cats C and D 1/8 SM and Circling Cats C and D 1/4 SM. In minimum visibility conditions bright lights on highway 1/4 mile north of airport may be mistaken for runway lights. Rwy 5 helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH: Climb to 2000 direct KISEC and hold.

AWOS-3	PALM BEACH APP CON	BOCA RATON TOWER★	GND CON	CLNC DEL	GCO
121.125	127.35 343.6	118.425 (CTAF) L	121.8	121.8	127.35





CATEGORY	A	B	C	D
LPV DA	283-7/8	271 (300-7/8)		
LNAV/VNAV DA	458-1 3/8	446 (500-1 3/8)		
LNAV MDA	440-1	428 (500-1)	440-1 1/4	428 (500-1 1/4)
C CIRCLING	680-1	667 (700-1)	680-1 3/4 667 (700-1 3/4)	880-2 3/4 867 (900-2 3/4)



SE-3, 18 APR 2024 to 16 MAY 2024
SE-3, 18 APR 2024 to 16 MAY 2024