

WAAS CH 58003 W14A	APP CRS 136°	Rwy Idg 5502 TDZE 583 Apt Elev 583
--	------------------------	---

RNAV (GPS) RWY 14

FREEMAN MUNI (SE.R)


RNP APCH - GPS.

NA


Baro-VNAV and VDP NA when using Louisville Muhammad Ali Intl altimeter setting. Rwy 14 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Louisville Muhammad Ali Intl altimeter setting and increase all DA 117 feet and all MDA 120 feet; increase LPV and LNAV/VNAV all Cats and LNAV and Circling Cats C/D visibility ¼ SM.

MISSED APPROACH:
Climb to 2400 direct ZEKAM and hold.

AWOS-3 119.425	INDIANAPOLIS CENTER 124.775 269.025	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



ELEV 583	TDZE 583
-----------------	-----------------



4 NM Holding Pattern RUYOT		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 24).		2400	ZEKAM
6000 ← 316°		TOLUY 2500		BEGND 3.2 NM to RW14	
2600 → 136°		2500		1.2 NM to RW14	
GP 3.00° TCH 40		1640		RW14	
6 NM		2.7 NM		2 NM	
CATEGORY A		CATEGORY B		CATEGORY C	
LPV DA		860-7/8		277 (300-7/8)	
LNAV/VNAV DA		1037-13/8		454 (500-13/8)	
LNAV MDA		980-1		397 (400-1)	
CIRCLING		1040-1		1300-2	
		457 (500-1)		717 (800-2)	
		1100-1		1300-2 ¼	
		517 (600-1)		717 (800-2 ¼)	