WAAS	APP CRS		
CH 56323	013°	Rwy Idg	6750
W01A		TDZE	2495
		Apt Elev	2504

RNAV (GPS) RWY 1

RALEIGH COUNTY MEML (BKW)

T A Baro-VNAV NA when using Bluefield altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 28°C (82°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter not received, use Bluefield altimeter setting and increase all DA 118 feet and all MDA 120 feet; increase LPV all Cats visibility ½ SM, LNAV/VNAV all Cats visibility ¼ SM, LNAV Cat C/D visibility ½ SM, and Circling Cat A/C visibility ¼ SM.

MISSED APPROACH: Climb to 5200 direct YISUK and hold.

ASOS	CHARLESTON APP CON	UNICOM
121.55	125.4 269.125	123.0 (CTAF) L



ELEV 2504 D TDZE 2495





CATEGORY	A	B	C	D
LPV DA	2810-1 315 (400-1)			
LNAV/VNAV DA	3093-2¼ 598 (600-2¼)			
LNAV MDA	3240-1 745 (800-1)	3240-1¼ 745 (800-1¼)	3240-2 745 (800-2)	
C CIRCLING	3240-1 736 (800-1)	3240-1¼ 736 (800-1¼)	3320-2½ 816 (900-2½)	3500-3 996 (1000-3)

NE-4, 18 APR 2024 to 16 MAY 2024
NE-4, 18 APR 2024 to 16 MAY 2024