WAAS	APP CRS	Rwy Idg	3998
CH **99335**	**301°**	TDZE	**2206**
W30A		Apt Elev	**2209**

RNAV (GPS) RWY 30

PHILIP (PHP)

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Pierre altimeter setting and increase all DA 204 feet and MDA 220 feet and increase LPV all Cats visibility ½ mile, increase LNAV/VNAV all Cats visibility 1 mile, increase LNAV Cat C visibility ½ mile, and increase Circling Cat C visibility ¾ mile. Helicopter visibility reduction below 1 SM NA. Procedure NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). Baro-VNAV NA when using Pierre altimeter setting.

MISSED APPROACH: Climb to 4500 direct CUSED and hold.

ASOS	DENVER CENTER	UNICOM
118.375	**127.95 338.2**	**122.8** (CTAF) L



ELEV 2209 TDZE 2206



MIRL Rwy 12-30 L



CATEGORY		A	B	C	D
LPV	DA	2456-1 250 (300-1)		2456-1⅜ 250 (300-1⅜)	NA
LNAV/VNAV	DA	2794-2 588 (600-2)			NA
LNAV MDA		2620-1 414 (500-1)		2620-1¼ 414 (500-1¼)	NA
C CIRCLING		2720-1 511 (600-1)	2760-1 551 (600-1)	2840-1¾ 631 (700-1¾)	NA

NC-1, 18 APR 2024 to 16 MAY 2024
NC-1, 18 APR 2024 to 16 MAY 2024