

WAAS CH 45927 W28A	APP CRS 279°	Rwy Idg TDZE 25 Apt Elev 41
--	------------------------	---

RNAV (GPS) RWY 28

NOME (OME)(PAOM)


RNP APCH - GPS.

Inop table does not apply to LPV 28 all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. Circling NA for Cats C and D north of Rwy 10-28. NA. Rwy 28 helicopter visibility reduction below 4000 NA. Circling Rwy 21 NA at night.

MALSR

MISSED APPROACH: Climb to 3700 direct SPYVY and hold, continue climb-in-hold to 3700.

AFIS 119.925	ANCHORAGE CENTER 133.3 290.4	NOME RADIO 123.6 (CTAF) 1
------------------------	--	-------------------------------------



ELEV 41

D

TDZE 25

REIL Rwy 3 and 10 1
HIRL Rwy 10-28 1
MIRL Rwy 3-21 1

	3700	SPYVY						
			FOVAG 2.3 NM to RW28	MUKDE 1700	EMMMO 4 NM Holding Pattern			
			1.2 NM to RW28	279°	099° → 3000			
			800	1700				GP 3.00° TCH 51
			1.2 NM	1.1 NM	2.8 NM	6.7 NM		
CATEGORY	A	B	C	D				
LPV DA		275/40	250 (300-¾)					
LNAV/VNAV DA		301/40	276 (300-¾)					
LNAV MDA		440/40	415 (400-¾)					
C CIRCLING	540-1	499 (500-1)	540-1½ 499 (500-1½)	700-2 659 (700-2)				