



LOC/DME I-ENA 108.9 Chan 26	APP CRS 196°	Rwy ldg 7575 TDZE 98 Apt Elev 100
---	------------------------	--

ILS Y or LOC Y RWY 20R
KENAI MUNI (ENA) (PAEN)

TACAN required. Circling NA to Rwy 2W and 20W. Circling Rwy 2R, 20L NA at night. For inop ALS, increase S-ILS 20R Cat E visibility to RVR 4000. For inop ALS, increase S-LOC 20R Cat E visibility to 1¼ SM. # RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 1800 then climbing right turn to 4000 on heading 046° and on EDF TACAN R-212 to TBONE INT/EDF 49.2 DME and hold. † Missed approach requires minimum climb of 800 feet per NM to 4000; if unable to meet climb gradient, see ILS Z or LOC Z RWY 20R.
--	----------------------	--

ATIS 133.35	ANCHORAGE CENTER 125.7 379.1	KENAI TOWER★ 121.3 (CTAF) 0 239.3	GND CON 118.75	KENAI RADIO 122.65
-----------------------	--	---	--------------------------	------------------------------



ELEV 100	D	TDZE 98
1800	4000	EDF R-212
196°	hdg 046°	TBONE INT
Use I-ENA DME when on the localizer course.		
*LOC only		
*I-ENA 2.6		
FREDE I-ENA 5.4		
1400		
196°		
016°		
4500		
2000		
GS 3.00°		
TCH 51		
CATEGORY	A	B
S-ILS 20R #†	298/24 200 (200-½)	
S-LOC 20R †	520/24 422 (500-½)	520/40 422 (500-¾)
CIRCLING	560-1 460 (500-1)	580-1 480 (500-1)
	580-1½ 480 (500-1½)	680-2 580 (600-2)
	760-2¼ 660 (700-2¼)	