



RNAV (GPS) RWY 2L
KENAI MUNI (ENA) (PAEN)

 Baro-VNAV NA when using Soldotna altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). When local altimeter setting not received, use Soldotna altimeter setting: increase LPV DA to 366 feet and LNAV/VNAV DA to 429 feet and all MDA 40 feet; increase LPV and LNAV/VNAV visibility all Cats and LNAV Cat C/D visibility ½ mile; increase Circling Cat D visibility ¼ mile. VDP NA when using Soldotna altimeter setting. Circling RWY 2R, 20L NA at night. Circling RWY 2W, 20W NA.

MISSED APPROACH:
Climb to 2000 direct
TBONE and hold.



CATEGORY	A	B	C	D
LPV DA	344- ³ / ₄ 250 (300- ³ / ₄)			
LNAV/ VNAV DA	407-1 313 (400-1)			
LNAV MDA	480-1 386 (400-1)		480-1 ¹ / ₈ 386 (400-1 ¹ / ₈)	
 CIRCLING	560-1 460 (500-1)	580-1 480 (500-1)	580-1 ¹ / ₂ 480 (500-1 ¹ / ₂)	740-2 640 (700-2)

AK. 21 MAR 2024 to 16 MAY 2024