

WAAS CH 45910 W26A	APP CRS 259°	Rwy Idg TDZE 174 Apt Elev 192
--	------------------------	---

RNAV (GPS) RWY 26

ILIAMNA (ILI) (PAIL)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -21°C or above 54°C. When local altimeter setting not received, procedure NA. Circling NA to waterways N, S, E, W.

-29°C

MISSED APPROACH: Climb to 600, then climbing left turn to 7000 direct NUTUW and hold, continue climb-in-hold to 7000.

AFIS
134.95

ANCHORAGE CENTER
118.8

ILIAMNA RADIO
123.6 (CTAF) 0

600

7000

NUTUW

028°

208°

7 NM

WAKNU

7 NM Holding Pattern

WOKAD
4.2 NM to RW26

JUSTM

WAKNU

0.8 NM to RW26

1500

2800

6100

GP 3.00°

TCH 35

CATEGORY	A	B	C	D
LPV DA	424-1 250 (300-1)			
LNAV/VNAV DA	424-1 250 (300-1)			
LNAV MDA	440-1 266 (300-1)			
CIRCLING	740-1 548 (600-1)		820-1¾ 628 (700-1¾)	1700-3 1508 (1600-3)

WATER RWYS:
N-S 2892 X 400
E-W 2998 X 400

REIL Rwy 26 and 36 0
MIRL Rwy 8-26 and 18-36 0

ELEV 192

TDZE 174