

TOP ALTITUDE:
ASSIGNED BY ATC

RNAV 1 - DME/DME/IRU or GPS.

RADAR required.

275°
275°

095°
095°

ATIS
125.025
CLNC DEL
118.25
GND CON
121.9
PONTIAC TOWER ★
120.5 (CTAF)
DETROIT DEP CON
132.35 284.0

TAKEOFF MINIMUMS:
Rwy 18, 36: NA - Environmental.
Rwy 9L/R, 27L/R: Standard with minimum
climb of 500' per NM to 1481.

NOTE: Turbojet departures at/above 10000,
maintain 280K until advised by ATC.
NOTE: For use by Cleveland terminal arrivals only.

KZLOV
10000
4000

148°

WINNZ

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 9L/R: Climb on heading 095° or as assigned for RADAR vectors to cross KZLOV at or above 4000 and at or below 10000, thence...
TAKEOFF RUNWAYS 27L/R: Climb on heading 275° or as assigned for RADAR vectors to cross KZLOV at or above 4000 and at or below 10000, thence...
....on track 148° to WINNZ. Maintain assigned altitude, expect filed altitude ten minutes after departure.

KZLOV ONE DEPARTURE (RNAV)

(KZLOV1.WINNZ) 14JUL22

PONTIAC, MICHIGAN
OAKLAND COUNTY INTL (PTK)

EC-1, 18 APR 2024 to 16 MAY 2024

EC-1, 18 APR 2024 to 16 MAY 2024