



LOC I-MDI 111.9	APP CRS 313°	Rwy Idg TDZE 7002 1389 Apt Elev 1391	ILS or LOC RWY 31 BEMIDJI RGNL (BJI)
---------------------------	------------------------	--	---

DME required. RADAR required for procedure entry.	MALSR	MISSED APPROACH: Climb to 2400 then climbing left turn to 3200 on heading 100° and IDJ VOR/DME R-135 to IBOME/IDJ 5.6 DME and hold.
Autopilot coupled approach NA below 2126. DME from IDJ VOR/DME. Simultaneous reception of I-MDI and IDJ DME required. For inop ALS, increase S-LOC 31 Cat C/D visibility to 1 SM.		

AWOS-3 119.275	MINNEAPOLIS CENTER 134.75 251.1	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



2400	3200	IDJ R-135	IBOME IDJ 5.6	IBOME IDJ 5.6	One Minute Holding Pattern
↑	hdg 100°			3200	
*LOC only					
				133°	5800 3200
				3200	GS 3.00° TCH 45
CATEGORY	A	B	C	D	
S-ILS 31	1589-½ 200 (200-½)				
S-LOC 31	1740-½ 351 (400-½)		1740-⅝ 351 (400-⅝)		