

LOC/DME I-ANE	APP CRS	Rwy Idg
111.15	269°	5000
Chan 48 (Y)		TDZE 910
		Apt Elev 912

ILS or LOC RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

DME required. RADAR required for procedure entry at BLAYN.

⚠

VDP NA when using Crystal altimeter setting. When local altimeter setting not received, use Crystal altimeter setting and increase S-ILS 27 DA to 1131 feet; increase all MDAs 40 feet and S-LOC 27 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. For inop ALS when using Crystal altimeter setting, increase S-LOC 27 Cat C/D visibility to 1 ½ SM.

MALSR

MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700.

ATIS	MINNEAPOLIS APP CON	ANOKA TOWER★	GND CON	CLNC DEL	CLNC DEL	UNICOM
120.625	126.5 335.65	132.4 (CTAF) 0	121.85	121.3	121.85 (When twr closed)	122.95

ELEV 912

TDZE 910

HIRL Rwy 9-27

MIRL Rwy 18-36

REIL Rwys 9, 18, and 36

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

2700	GEP	Use I-ANE DME when on the localizer course.				JUDAL
						I-ANE 16.7
		KOGGE	BOKYA			
		I-ANE 3.6	I-ANE 6.2			
				2600		3100
				2600		
				1780		
				1.2 NM	1.4 NM	2.6 NM
						10.5 NM
CATEGORY	A	B	C	D		
S-ILS 27	1110-½ 200 (200-½)					
S-LOC 27	1340-½	430 (500-½)	1340-¾	430 (500-¾)		
CIRCLING	1400-1	488 (500-1)	1420-1½	1580-2		
			508 (600-1½)	668 (700-2)		

MINNEAPOLIS, MINNESOTA

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

Amdt 1 08SEP22

45°09'N-93°13'W

ILS or LOC RWY 27