ILS or LOC RWY 5

LAKE CUMBERLAND RGNL (SME)

LOC/DME I-SME	APP CRS	Rwy Idg	5287
109.3	048°	TDZE	927
Chan 30		Apt Elev	927

DME required. ADF required.

Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Monticello altimeter setting and increase S-ILS 5 DA to 1526 feet and all visibilities ⅛ SM. Increase all MDAs 60 feet and S-LOC 5 visibility Cat C/D ⅛ SM, and Circling visibility Cat B ¼ SM. VDP NA when using Monticello altimeter setting.

MISSED APPROACH: Climb to 2000 then climbing right turn to 3000 direct CDX NDB and hold, continue climb-in-hold to 3000.

AWOS-3	INDIANAPOLIS CENTER	UNICOM
120.05	124.625 371.925	122.8 (CTAF) L



CATEGORY	A	B	C	D
S-ILS 5	1482-1⅝ 555 (600-1⅝)			
S-LOC 5	1540-1 613 (700-1)		1540-1¾ 613 (700-1¾)	
CIRCLING	1620-1 693 (700-1)	1720-1 793 (800-1)	2100-3 1173 (1200-3)	

SE-1, 18 APR 2024 to 16 MAY 2024
SE-1, 18 APR 2024 to 16 MAY 2024