WAAS	APP CRS	Rwy Idg	3800
CH 60934	004°	TDZE	832
W36A		Apt Elev	835

RNAV (GPS) RWY 36

DUPONT/LAPEER (D95)

DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Flint altimeter setting and increase all MDA 60 feet and increase LNAV Cat C visibility ⅛ mile and LP Cat C and Circling Cat C visibility ¼ mile. Circling NA to Rwys 9 and 27.

MISSED APPROACH: Climb to 3000 direct WIVGU and hold.

AWOS-3P	GREAT LAKES APP CON ★	UNICOM
134.050	118.8 257.9	123.0 (CTAF) L



ELEV 835 TDZE 832

MIRL Rwy 18-36 L

REIL Rwys 18 and 36 L





CATEGORY	A	B	C	D
LP MDA	1220-1 388 (400-1)		1220-1⅛ 388 (400-1⅛)	NA
LNAV MDA	1260-1 428 (500-1)		1260-1¼ 428 (500-1¼)	NA
C CIRCLING	1300-1 465 (500-1)	1380-1 545 (600-1)	1460-1¾ 625 (700-1¾)	NA

EC-1, 18 APR 2024 to 16 MAY 2024
EC-1, 18 APR 2024 to 16 MAY 2024