

WAAS CH 69423 W28A	APP CRS 284°	Rwy Idg TDZE 1189 Apt Elev 1191	5504
--	------------------------	---	-------------

RNAV (GPS) RWY 28

KNOX COUNTY (4I3)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.

MISSED APPROACH: Climb to 3000 direct BONIF and hold.

AWOS-3 126.05	COLUMBUS APP CON 125.95 317.775	CLNC DEL 119.45	UNICOM 123.05 (CTAF) 0
-------------------------	---	---------------------------	---

MISSED APCH FIX

BONIF

104°

284°

4 NM

MSA RW 28 25 NM

3100

1640 Δ

Δ 1497 $\pm$

Δ 1330

1273 $\pm$

1721

RW28

SLAPT
1.7 NM to RW28

(FAF) WEBUB

2700

284°
(6.9)

(IF/IAF) PATIE

4 NM

HOLD $\overline{6000}$
 $\overline{2800}$

Procedure NA for arrival on APE VORTAC airway radials 055 CW 168.

APPLETON APE

3000
099°
(13.5)

2800 NoPT
014°
(9.8)

(IAF) TUCUG

2800 NoPT
305°
(13.6)

(IAF) ROSCO

ELEV 1191

TDZE 1189

10

5504 X 100

28

284°

3000

BONIF

*LNAV only

SLAPT
1.7 NM to RW28

*1 NM to RW28

RW28

*1760

2700

WEBUB

2700

PATIE

4 NM Holding Pattern

104°

284°

$\overline{6000}$
 $\overline{2800}$

GP 3.00°
TCH 40°

CATEGORY	A	B	C	D
LPV DA		1389-1	200 (200-1)	
LNAV/VNAV DA		1439-1	250 (300-1)	
LNAV MDA		1540-1	351 (400-1)	

MIRL Rwy 10-28 **0**

REIL Rwys 10 and 28 **0**

EC-2, 18 APR 2024 to 16 MAY 2024

EC-2, 18 APR 2024 to 16 MAY 2024

MOUNT VERNON, OHIO

Amtd 1D 07NOV19

40°20'N-82°32'W

KNOX COUNTY (4I3)

RNAV (GPS) RWY 28