WAAS	APP CRS	Rwy Idg	5000
CH 90409	120°	TDZE	1274
W12A		Apt Elev	1274

RNAV (GPS) RWY 12

DENISON MUNI (DNS)

RNP APCH-GPS.

Circling NA to Rwys 18 and 36. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro-VNAV and VDP NA when using Carroll altimeter setting. When local altimeter setting not received, use Carroll altimeter setting; increase LPV DA 1596 feet, LNAV/VNAV DA to 1626 feet; increase all MDAs 80 feet and visibility LNAV Cat C ⅛ SM and Circling Cat C ¼ SM.

MISSED APPROACH: Climb to 3900 direct OTLAZ and hold.

AWOS-3	MINNEAPOLIS CENTER	UNICOM
119.95	119.6 290.4	122.8 (CTAF) L



ELEV 1274	TDZE 1274



MIRL Rwy 12-30 L
REIL Rwys 12 and 30 L



CATEGORY	A	B	C	D
LPV DA	1524-1 250 (300-1)			NA
LNAV/VNAV DA	1554-1 280 (300-1)			NA
LNAV MDA	1860-1 586 (600-1)		1860-1¾ 586 (600-1¾)	NA
CIRCLING	1860-1 586 (600-1)	1880-1 606 (700-1)	2100-2½ 826 (900-2½)	NA

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024