

WAAS CH 99436 W35A	APP CRS 354°	Rwy Idg 5506 TDZE 1155 Apt Elev 1160
--	------------------------	---

RNAV (GPS) RWY 35
STROTHER FLD (WLD)

RNP APCH.

▼ Baro-VNAV and VDP NA when using Wichita Dwight D Eisenhower Ntl altimeter setting.
▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Wichita Dwight D Eisenhower Ntl altimeter setting: increase LPV DA to 1509 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1557 feet and all visibilities ¼ SM; increase all MDA 120 feet, LNAV Cat C visibility ¾ SM and Circling Cat C visibility ½ SM.

MISSED APPROACH:
Climb to 3600 direct
ECUWO and hold.

ASOS 118.025	KANSAS CITY CENTER 127.8 319.1	UNICOM 122.8 (CTAF) 0
------------------------	--	--

MISSED APCH FIX

3600	ECUWO
	

* LNAV only.

*1.4 NM to RW35

$$\frac{\text{GP } 3.00^\circ}{\text{TCH } 54}$$

CATEGORY		A	B	C	D
LPV	DA	1405-3/4 250 (300-3/4)			NA
LNAV/ VNAV	DA	1453-1 298 (300-1)			NA
LNAV MDA		1640-1 485 (500-1)		1640-1 3/8 485 (500-1 3/8)	NA
 CIRCLING		1680-1 520 (600-1)		1680-1 1/2 520 (600-1 1/2)	NA

ELEV 1160

TDZE 1155

35

1

5506 X 100

3120 X 75

0.2% Up

1230

354° to RW35

MIRL Rwy 13-31

HIRL Rwy 17-35

REIL Rwy 17 and 35