| WAAS CH 77599 W02A | APP CRS 021° | Rwy ldg 7401<br>TDZE 889<br>Apt Elev 889 |
|---|---|---|

# RNAV (GPS) RWY 2
## COLUMBIA RGNL (COU)

RNP APCH-GPS.

Circling NA for Cat D west of Rwys 2 and 13. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000 and increase LNAV Cat C/D visibility to RVR 5500.
*RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3100 direct AGVOY and hold.

| ATIS | MIZZU APP CON | COLUMBIA TOWER* | GND CON | UNICOM |
|---|---|---|---|---|
| 128.45 | 124.375 353.925 | 119.3 (CTAF) L 363.25 | 121.6 | 122.95 |




ELEV 889 D TDZE 889




| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA* | 1089/24 200 (200-½) | | | |
| LNAV/VNAV DA | 1143/24 254 (300-½) | | | |
| LNAV MDA | 1240/24 351 (400-½) | | 1240/30 351 (400-⅝) | |
| C CIRCLING | 1280-1 391 (400-1) | 1340-1 451 (500-1) | 1360-1½ 471 (500-1½) | 1440-2 551 (600-2) |



NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024