WAAS	APP CRS		
CH **56522**	**190°**	Rwy Idg	**5001**
W19A		TDZE	**1245**
		Apt Elev	**1255**

RNAV (GPS) RWY 19

NEOSHO HUGH ROBINSON (EOS)

When VGSI inop, Circling Rwy 1 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Joplin altimeter setting and increase all DA 87 feet and all MDA 100 feet; increase LPV all Cats visibility ⅛ mile, LNAV/VNAV all Cats visibility ⅜ mile, and LNAV Cat C visibility ¼ mile. VDP and Baro-VNAV NA when using Joplin altimeter setting.

MISSED APPROACH: Climb to 3300 direct RUKOC and hold.

KANSAS CITY CENTER	AUNICOM
128.6 282.325	**122.8** (CTAF) L



CATEGORY	A	B	C	D
LPV DA	1495-1 250 (300-1)			NA
LNAV/VNAV DA	1692-1½ 447 (500-1½)			NA
LNAV MDA	1640-1 395 (400-1)		1640-1¼ 395 (400-1¼)	NA
CIRCLING	1720-1 465 (500-1)	1740-1 485 (500-1)	1740-1½ 485 (500-1½)	NA

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024