NDB TII	APP CRS	Rwy Idg	4000
269	250°	TDZE	785
		Apt Elev	786

NDB RWY 24
SENECA COUNTY (16G)

Rwy 24 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Findlay altimeter setting and increase all MDAs 60 feet, increase S-24 Cat C visibility ⅛ SM, and Circling Cat D visibility ¼ SM. Straight-in Rwy 24 NA at night, Circling Rwy 24 NA at night.

NA

MISSED APPROACH: Climb to 2400 then right turn direct TII NDB and hold.

AWOS-3	FDY ASOS	TOLEDO APP CON	UNICOM
127.175	132.85	120.8 317.55	123.0 (CTAF) L





1667

ELEV 786 TDZE 785







CATEGORY	A	B	C	D
S-24	1460-1	675 (700-1)	1460-1⅞ 675 (700-1⅞)	1460-2 675 (700-2)
CIRCLING	1460-1	674 (700-1)	1460-2 674 (700-2)	1560-2½ 774 (800-2½)

MIRL Rwy 6-24 L
REIL Rwys 6 and 24 L

EC-2, 18 APR 2024 to 16 MAY 2024
EC-2, 18 APR 2024 to 16 MAY 2024