RNAV (GPS) RWY 14

DESTIN EXEC (DTS)

WAAS	APP CRS	Rwy Idg	5001
CH 48923	143°	TDZE	22
W14A		Apt Elev	22

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 0°C (32°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Crestview altimeter setting. Rwy 14 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Crestview altimeter setting and increase all DA/MDA 80 feet; increase LPV all Cats visibility ⅛ SM, LNAV/VNAV all Cats visibility ⅜ SM, increase LNAV Cats C and D ⅛ SM, and Circling Cats C and D ¼ SM.

MISSED APPROACH: Climb to 2000 direct AJLIP and hold.

ATIS	EGLIN APP CON	DESTIN TOWER ★	GND CON	CLNC DEL	CLNC DEL	UNICOM
133.925	132.1 360.6	118.45 (CTAF) L	121.6	121.6	127.7 377.2 (When twr closed)	123.075



ELEV 22 TDZE 22



HIRL Rwy 14-32 L



CATEGORY	A	B	C	D
LPV DA	272-1	250 (300-1)		
LNAV/VNAV DA	367-1⅛	345 (400-1⅛)		
LNAV MDA	460-1	438 (500-1)	460-1¼	438 (500-1¼)
C CIRCLING	580-1	558 (600-1)	680-1¾ 658 (700-1¾)	680-2 658 (700-2)

SE-3, 18 APR 2024 to 16 MAY 2024
SE-3, 18 APR 2024 to 16 MAY 2024