LOC/DME RWY 36

GEORGE M BRYAN (STF)

LOC/DME I-STF	APP CRS	Rwy Idg	5550
109.9	360°	TDZE	326
Chan 36		Apt Elev	333

DME Required. When local altimeter setting not received, use Golden Triangle altimeter setting and increase all MDA 40 feet; increase S-36 Cats C/D visibility ⅛ mile and Circling Cat C visibility ¼ mile. VDP NA when using Golden Triangle altimeter setting.

MISSED APPROACH: Climb to 1000, then climbing left turn to 2400 on IGB VORTAC R-266 to NEEON/IGB 30 DME and hold.

AWOS-3PT	COLUMBUS APP CON ★	CLNC DEL	UNICOM
118.975	135.6 323.275	126.25	122.7 (CTAF)

RADAR REQUIRED

086° 266° NEEON IGB 30

LOCALIZER 109.9 I-STF Chan 36

719 552 500 830 649 464 600 1759

R-266

BIGBEE 116.2 IGB Chan 109

UZWIR I-STF 3.5

SOUER I-STF 6.2 RADAR

(6) 2000 360°

(IF/IAF) FEXIS I-STF 12.2 RADAR

180° 1 min 360° 180°

ALTERNATE MISSED APCH FIX

114.7 SQS 086° R-086 266° Chan 94 NEEON SQS 59

MSA IGB 25 NM 115° 3400 2100 360°

R-4404 B & C

ELEV 333 TDZE 326

18 5550 X 150 36 360°

REIL Rwy 36 L

HIRL Rwy 18-36 L

1000 2400 IGB R-266 NEEON

SOUER I-STF 6.2 RADAR

FEXIS I-STF 12.2 RADAR One Minute Holding Pattern

UZWIR I-STF 3.5

I-STF 2.1

I-STF 1

3.00° TCH 40

360° 180° 360° 3000 2000 1140

1.1 NM 1.4 NM 2.7 NM 6 NM

CATEGORY	A	B	C	D
S-36	720-1	395 (400-1)	720-1⅛	395 (400-1⅛)
C CIRCLING	920-1	587 (600-1)	920-1½ 587 (600-1½)	1020-2¼ 687 (700-2¼)

SC-4, 18 APR 2024 to 16 MAY 2024
SC-4, 18 APR 2024 to 16 MAY 2024