WAAS	APP CRS	Rwy Idg	5849
CH 86229	179°	TDZE	71
W18A		Apt Elev	75

RNAV (GPS) RWY 18

ST LANDRY PARISH (OPL)

T NA Baro-VNAV NA when using Lafayette altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). When VGSI inop, Straight-in/Circling Rwy 18 procedure NA at night. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. Circling to Rwy 6/24 NA at night. When local altimeter setting not received, use Lafayette altimeter setting: Increase LPV DA to 377 feet, LNAV/VNAV DA to 442 feet, and visibility LNAV/VNAV all Cats ¼ SM; increase all MDA 60 feet and visibility LNAV Cat C and D and Circling Cat C and D ¼ SM.

MISSED APPROACH: Climb to 2300 direct YOLUG and hold.

AWOS-3PT	LAFAYETTE APP CON ★	UNICOM
118.775	128.7 268.7	123.0 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	321-1 250 (300-1)			
LNAV/VNAV DA	386-1 315 (400-1)			
LNAV MDA	480-1 409 (500-1)		480-1⅛ 409 (500-1⅛)	
CIRCLING	780-1 705 (800-1)		780-2 705 (800-2)	920-2¾ 845 (900-2¾)



REIL Rwys 18 and 36 L
MIRL Rwy 18-36 L

SC-4, 18 APR 2024 to 16 MAY 2024
SC-4, 18 APR 2024 to 16 MAY 2024