

APP CRS
345°

Rwy Idg
TDZE
246

5119
246
246

RNAV (GPS) RWY 35

BARNWELL RGNL (BNL)


▽

NA

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Augusta Rgnl at Bush Fld altimeter setting and increase all MDAs 100 feet and increase LNAV Cat C/D visibilities ¼ mile. Circling Cat C visibility ¼ mile and Cat D visibility ½ mile. VDP NA when using Augusta Rgnl at Bush Fld altimeter setting.

MISSED APPROACH: Climb to 2200 direct FATSU and hold.

AWOS-3 119.775	JACKSONVILLE CENTER 132.925 363.2	GCO 121.725	UNICOM 122.8 (CTAF) 0
-------------------	--------------------------------------	----------------	--------------------------



ELEV 246

TDZE 246

REIL Rwy 17

MIRL Rwy 17-35 0

2200

FATSU

1.8 NM to RW35

3.04°

TCH 42

1.8

2.9 NM

6.3 NM

CULPA

4 NM Holding Pattern

165°

345°

2100

CATEGORY	A	B	C	D
LNAV MDA	860-1 614 (700-1)	860-1 614 (700-1)	860-1 614 (700-1 3/4)	860-2 614 (700-2)
CIRCLING	860-1 614 (700-1)	860-1 614 (700-1)	900-1 654 (700-1 3/4)	900-2 654 (700-2)