WAAS CH 69624 W09A	APP CRS 088°	Rwy ldg 5000 TDZE 2933 Apt Elev 2933

RNAV (GPS) RWY 9
GARRETT COUNTY (2G4)

Baro-VNAV and VDP NA when using Morgantown altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20° (-4°F) or above 54°C (130°F). Helicopter visibility reduction below ¾ SM NA. DME/DME RNP -0.3 NA. When local altimeter setting not received, use Morgantown altimeter setting and increase all DA and MDA 300 feet. Increase LPV and LNAV/VNAV all Cats visibility 1⅛ mile, LNAV Cat C visibility ⅞ mile and Circling Cat C visibility 1 mile.

NA

MISSED APPROACH: Climb to 5600 direct HABEX and hold.

AWOS-3	CLARKSBURG APP CON ★	UNICOM
120.125	119.425 284.65	123.0 (CTAF) L



ELEV 2933 TDZE 2933



CATEGORY	A	B	C	D
LPV DA	3183-¾ 250 (300-¾)			NA
LNAV/VNAV DA	3183-¾ 250 (300-¾)			NA
LNAV MDA	3300-1 367 (400-1)			NA
C CIRCLING	3340-1 407 (500-1)	3400-1 467 (500-1)	3500-1½ 567 (600-1½)	NA

REIL Rwys 9 and 27 L
MIRL Rwy 9-27 L

NE-3, 18 APR 2024 to 16 MAY 2024