LOC I-FQR	APP CRS	Rwy Idg	5000
111.1	017°	TDZE	361
		Apt Elev	365

LOC RWY 2

FITZGERALD MUNI (FZG)

Circling NA to Rwys 15 and 33. ADF required. When local altimeter setting not received, use Tifton altimeter setting and increase all MDA 60 feet, increase S-LOC 2 Cat C and D visibility ⅛ SM and Circling Cat C and D visibility ¼ SM.

ODALS

MISSED APPROACH: Climb to 900 then climbing right turn to 2000 direct SUR NDB and hold.

AWOS-3	JACKSONVILLE CENTER	UNICOM
118.625	127.575 269.025	123.0 (CTAF) L

Procedure NA for arrival on VNA VORTAC airway radials 127 CW 178.

VIENNA 116.5 VNA Chan 112

2000 162° (37.5)

MSA SUR 25 NM 2500

790

LOCALIZER 111.1 I-FQR

460±

411±

463±

197°

ADF REQUIRED

IAF FITZGERALD 362 SUR

017°

(CFBXH)

242° 062°

197°

935

Remain within 10 NM

SUR NDB

197°

2000

017°

1700

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 44).

3.16° TCH 40

3.9 NM

900	2000	SUR
↑	↗	○

ELEV 365 TDZE 361

20

5000 X 101

2984 X 300

0.8% UP

2

017°

MIRL Rwy 2-20 L

REIL Rwy 2 L

CATEGORY	A	B	C	D
S-LOC 2	720-¾ 359 (400-¾)		720-⅞ 359 (400-⅞)	
C CIRCLING	880-1 515 (600-1)		1160-2¼ 795 (800-2¼)	1160-2½ 795 (800-2½)

FAF to MAP 3.9 NM

Knots	60	90	120	150	180
Min:Sec	3:54	2:36	1:57	1:34	1:18

SE-4, 18 APR 2024 to 16 MAY 2024
SE-4, 18 APR 2024 to 16 MAY 2024