

VENICE, FLORIDA

AL-5960 (FAA)

23166

WAAS CH 53433 W23A	APP CRS 230°	Rwy Idg 4377 TDZE 18 Apt Elev 18
--	------------------------	---

RNAV (GPS) RWY 23


VENICE MUNI (VNC)

T When local altimeter setting not received, use Sarasota altimeter setting and increase all MDA 60 feet and increase LP and LNAV Cats C, D visibility $\frac{1}{8}$ mile, and Circling Cat C visibility $\frac{1}{4}$ mile.


A DME/DME RNP-0.3 NA. VDP NA with Sarasota altimeter setting. Helicopter visibility reduction below $\frac{3}{4}$ SM NA.

MISSED APPROACH:
Climb to 2900 direct
WUPOS and hold.

AWOS-3 119.275	TAMPA APP CON 119.65 353.575	CLNC DEL 118.075	UNICOM 122.725 (CTAF) ①
--------------------------	--	----------------------------	-----------------------------------



2900 ↑	WUPOS ✦	4 NM Holding Pattern			
CATEGORY	A	B	C	D	
LP MDA	360-1 342 (400-1)				
LNAV MDA	440-1	422 (500-1)	440-1¼	422 (500-1¼)	
C CIRCLING	500-1	482 (500-1)	700-2 682 (700-2)	920-3 902 (1000-3)	



VENICE, FLORIDA
Orig-B 16OCT14

27°04'N-82°26'W

VENICE MUNI (VNC)

RNAV (GPS) RWY 23

SE-3, 18 APR 2024 to 16 MAY 2024