

WAAS
CH **70614**
W17A

APP CRS
172°

Rwy Idg
TDZE **2176**
Apt Elev **2189**

RNAV (GPS) RWY 17
WEST WOODWARD (WWR)

RNP APCH

Baro-VNAV and VDP NA when using Gage altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use Gage altimeter setting and increase all DA/MDA 40 feet. Inop table does not apply. Circling Rwy 5, 23 NA at night.

ODALS

MISSED APPROACH:
Climb to 4500 direct
TISSY and hold.

AWOS-3 118.425	KANSAS CITY CENTER 126.95 379.2	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------

ELEV 2189	TDZE 2176
172°	352°
2500 X 60	5500 X 100
2230	35
REIL Rwy 35 0	MIRL Rwy 5-23 and 17-35 0
4500	TISSY
*LNAV only.	*1.6 NM to RWY 17
RWY 17	RUNSY
3800	OHFEB
1.6 NM	3.4 NM
6.1 NM	4 NM Holding Pattern
GP 3.00°	TCH 39
CATEGORY	A
LPV DA	2426-1 250 (300-1)
LNAV/VNAV DA	2572-1½ 396 (400-1½)
LNAV MDA	2700-1 524 (600-1) 2700-1½ 524 (600-1½) 2700-1¾ 524 (600-1¾)
CIRCLING	2700-1 511 (600-1) 2860-1 671 (700-1) 2940-2¼ 751 (800-2¼) 2960-2½ 771 (800-2½)

WOODWARD, OKLAHOMA

Orig-B 07OCT21

36°26'N-99°31'W

WEST WOODWARD (WWR)

RNAV (GPS) RWY 17