

APP CRS
260°

Rwy Idg
TDZE
Apt Elev

6500
3212
3261

RNAV (GPS) RWY 27

SAN CARLOS APACHE (P13)

RNP APCH.


▼

NA

Rwy 27 helicopter visibility reduction below ¾ SM NA.
VDP NA when using San Manuel altimeter setting. When local altimeter setting not received, use San Manuel altimeter setting and increase all MDA 120 feet.

MISSED APPROACH: (Do not exceed 175K until IFURI) Climb to 4600 then climbing right turn to 7200 direct IFURI and hold, do not exceed 230K when continuing climb-in-hold to 7200.
*Missed approach requires minimum climb of 290 feet per NM to 5340.

AWOS-3 120.075	ALBUQUERQUE CENTER 125.4 269.3	UNICOM 122.8 (CTAF) 0
-------------------	-----------------------------------	--------------------------



4600

7200

IFURI

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 43).

WUNVO
2.9 NM to
GOBFO

HURFY

IFURI

7 NM
Holding Pattern

1.1 NM to
GOBFO

GOBFO

4780

5800

10000

7200

0.6

1.1 NM

1.8 NM

2.3 NM

4.8 NM

CATEGORY

A

B

C

D

LNAV MDA*

3760-1

548 (500-1)

NA

LNAV MDA

4180-1¼
968 (1000-1¼)

4180-1½
968 (1000-1½)

NA

CIRCLING

4180-1¼
919 (1000-1¼)

4180-1½
919 (1000-1½)

NA

MIRL Rwy 9-27 0

REIL Rws 9 and 27