

RNAV 1 - DME/DME/IRU or GPS.

RADAR required.

TOP ALTITUDE:

3000

CHARLOTTE DEP CON

128.325 307.8

AWOS-3

128.175

CLNC DEL

121.75 254.375

GND CON

121.75 254.375

STANLY COUNTY TOWER★

126.275 (CTAF) 291.9

TAKEOFF MINIMUMS

Rwys 4L, 22R: NA-Environmental.

Rwy 22L: Standard.

Rwy 4R: 300-1¾ or standard with minimum

climb of 315' per NM to 1000.

LAMDE

114°

(11)

LILLS

NOTE: For turbo jets only.

NOTE: Transponder code will be issued via PDC or Charlotte CLNC DEL.

NOTE: If unable to accept climb rates, advise ATC on initial contact.

NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

MSA VUJ 25 NM

3100

NOTE: Chart not to scale.

▼

DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, on RADAR vectors to LAMDE, then on depicted route to LILLS. Maintain 3000. Expect clearance to filed altitude within 10 minutes after departure.

LILLS THREE DEPARTURE (RNAV)
(LILLS3.LILLS) 21MAR24

ALBEMARLE, NORTH CAROLINA
STANLY COUNTY (VUJ)

SE-2, 18 APR 2024 to 16 MAY 2024

SE-2, 18 APR 2024 to 16 MAY 2024