RNAV (GPS) RWY 28

JOHN EDWIN JONES SR FLD/METTER MUNI (MHP)

WAAS	APP CRS	Rwy Idg	5001
CH 78438	280°	TDZE	197
W28A		Apt Elev	197

T
NA

Baro-VNAV NA. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. Use Claxton altimeter setting; when not received, use Vidalia altimeter setting and increase LPV DA to 500, LNAV/VNAV DA to 533, increase all MDA 20 feet, increase LNAV/VNAV all Cats and LNAV Cat C/D visibility ⅛ mile and Circling Cat C/D visibility ¼ mile.

MISSED APPROACH: Climb to 700 then climbing left turn to 3000 direct LOTTS and hold.

AWOS-3PT	CWV AWOS-3	JACKSONVILLE CENTER	UNICOM
120.3	120.075	132.925 363.2	123.0 (CTAF) L



ELEV 197 TDZ 197



MIRL Rwy 10-28 L
REIL Rwy 10 L



CATEGORY	A	B	C	D
LPV DA	494-1 297 (300-1)			
LNAV/VNAV DA	527-1 330 (400-1)			
LNAV MDA	620-1 423 (500-1)		620-1¼ 423 (500-1¼)	
C CIRCLING	820-1 623 (700-1)	880-1 683 (700-1)	1060-2½ 863 (900-2½)	1060-2¾ 863 (900-2¾)

SE-4, 18 APR 2024 to 16 MAY 2024
SE-4, 18 APR 2024 to 16 MAY 2024