


WAAS CH 86625 W20A	APP CRS 198°	Rwy Idg 6001 TDZE 501 Apt Elev 501
--	------------------------	---

RNAV (GPS) RWY 20

JOHN C TUNE (JWN)

 NA	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Nashville Intl altimeter setting and increase all DA 40 feet and all visibilities $\frac{1}{8}$ mile; increase all MDA 40 feet and LNAV Cats C and D visibility $\frac{1}{8}$ mile. Circling NA east of Rwy 2-20. Baro-VNAV and VDP NA when using Nashville Intl altimeter setting. Helicopter visibility reduction below $\frac{3}{4}$ SM NA.					MISSED APPROACH: Climb to 1200 then climbing right turn to 3000 direct BEVEE and hold.	
	ATIS 127.075	NASHVILLE APP CON 119.35 372.0	JOHN TUNE TOWER ★ 119.45 (CTAF) 0	GND CON 121.7	CLNC DEL 121.7	CLNC DEL 124.55 (when twr closed)	UNICOM 122.7



MIRL Rwy 2-20
REIL Rwys 2 and 20

CATEGORY	A	B	C	D
LPV DA		856-1¼	355 (400-1¼)	
LNAV/VNAV DA		1003-1¾	502 (600-1¾)	
LNAV MDA	1120-1	619 (700-1)	1120-1¾	619 (700-1¾)
C CIRCLING	1200-1	699 (700-1)	1340-2½ 839 (900-2½)	1340-2¾ 839 (900-2¾)