RNAV (GPS) RWY 5

MARION COUNTY (X35)

WAAS	APP CRS	Rwy Idg	5000
CH 72946	050°	TDZE	65
W05A		Apt Elev	65

RNP APCH - GPS.

NA Rwy 5 helicopter visibility reduction below 1 SM NA. Use Ocala altimeter setting; when not received, use Leesburg altimeter setting and increase all MDAs 60 feet and LNAV and LP visibility Cat C/D ¼ SM and Circling visibility Cat D ¼ SM. Straight-in Rwy 5 NA at night, Circling Rwy 5, 10, 28 NA at night.

MISSED APPROACH: Climb to 600 then climbing left turn to 1700 direct EMMIT and hold.

OCF AWOS-3PT	JACKSONVILLE APP CON	UNICOM
128.125	118.6 251.15	122.8 (CTAF) L



ELEV 65 TDZE 65



CATEGORY	A	B	C	D
LP MDA	500-1	435 (500-1)	500-1¼	435 (500-1¼)
LNAV MDA	540-1	475 (500-1)	540-1⅜	475 (500-1⅜)
CIRCLING	540-1	475 (500-1)	580-1½ 515 (600-1½)	760-2¼ 695 (700-2¼)



MIRL Rwy 5-23 and 10-28 L

SE-3, 18 APR 2024 to 16 MAY 2024
SE-3, 18 APR 2024 to 16 MAY 2024