

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Vicksburg Muni, MS altimeter setting and increase LPV DA to 309 feet, LNAV/VNAV DA to 516 feet all visibilities ¼ mile; increase all MDA 40 feet and visibility Cats C/D ¼ mile. Baro-VNAV and VDP NA with Vicksburg Muni, MS altimeter setting.

SSALR

MISSED APPROACH:

Climb to 2000 direct DEXIW and hold.

ASOS	MEMPHIS CENTER	UNICOM
118.525	132.5 259.1	123.0 (CTAF) 0

MISSED APCH FIX

870A

		*LNAV only				
			JANLU 1.4 NM to RW36	WEJJI 1700	YAYDI	4 NM Holding Pattern
			*1.1 NM to RW36	357°	177°	2000
			580*	1700	GP 3.00°	TCH 49
			1.1 NM	0.3 NM	3.5 NM	6.9 NM
CATEGORY		A	B	C	D	
LPV DA			286-½	200 (200-½)		
LNAV/VNAV DA			493-¾	407 (500-¾)		
LNAV MDA		480-½	394 (400-½)	480-⅝	394 (400-⅝)	
CIRCLING		540-1	454 (500-1)	720-1¾ 634 (700-1¾)	720-2 634 (700-2)	

ELEV 86

TDZE 86

REIL Rwy 18 0

MIRL Rwy 18-36 0

TALLULAH, LOUISIANA

Amdt 4 15SEP16

32°21'N-91°02'W

VICKSBURG TALLULAH RGNL (TVR)

RNAV (GPS) RWY 36