

WAAS CH 45721 W23A	APP CRS 233°	Rwy Idg TDZE 210 Apt Elev 215
--	------------------------	---

RNAV (GPS) RWY 23

EARLY COUNTY (BIJ)

RNP APCH - GPS.

▼


▲

Inop table does not apply to LPV, LNAV/VNAV and LNAV Cat A/B. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Rwy 23 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Bainbridge altimeter setting; increase LPV DA to 578 feet, LNAV/VNAV DA to 587 feet; increase all MDAs 80 feet and visibility LNAV Cat C/D ½ SM and Circling Cat C/D ¼ SM. For inop ALS, increase LNAV Cat C/D visibility to 1 ½ SM. Baro-VNAV and VDP NA when using Bainbridge altimeter setting.


MALSF

MISSED APPROACH:
Climb to 2000 direct
ENUCI and hold.

AWOS-3PT 118.475	CAIRNS APP CON ★ 125.4 327.125	CTAF 122.9 0
----------------------------	--	------------------------



ELEV 215	TDZE 210
----------	----------



2000	ENUCI	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).		4 NM Holding Pattern
↑	✦			
*LNAV only.		NINVE 2.5 NM to RW23	EARLY 1800	PARGE
		1.1 NM to RW23	1040	053° → ← 233° 3000
		1.1	1.4	GP 3.00° TCH 57
		2.3 NM		6.7 NM
CATEGORY	A	B	C	D
LPV DA		501-1	291 (300-1)	
LNAV/ VNAV DA		510-1	300 (300-1)	
LNAV MDA		600-1	390 (400-1)	
CIRCLING	720-1	505 (600-1)	860-1¾ 645 (700-1¾)	960-2½ 745 (800-2½)