| WAAS | APP CRS | Rwy Idg | 3700 |
|---|---|---|---|
| CH 99630 | 100° | TDZE | 1777 |
| W09A | | Apt Elev | 1779 |

# RNAV (GPS) RWY 9
## LINTON MUNI (7L2)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Bismarck Muni altimeter setting: increase LPV DA to 2134 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 2198 and all visibilities ½ SM; increase all MDAs 120 feet and visibility LNAV Cat C ¼ SM and Circling Cat C ½ SM. Baro-VNAV and VDP NA when using Bismarck Muni altimeter setting.

MISSED APPROACH: Climb to 4700 direct JUTIL and on track 018° to WISEK and hold.

| ASOS-3 | MINNEAPOLIS CENTER | CTAF |
|---|---|---|
| 118.175 | 135.25 256.7 | 122.9 L |










| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 2027-1 250 (300-1) | | | NA |
| LNAV/VNAV DA | 2091-1 314 (400-1) | | | NA |
| LNAV MDA | 2160-1 383 (400-1) | | 2160-1⅛ 383 (400-1⅛) | NA |
| CIRCLING | 2220-1 441 (500-1) | 2360-1 581 (600-1) | 2440-1¾ 661 (700-1¾) | NA |



NC-1, 18 APR 2024 to 16 MAY 2024
NC-1, 18 APR 2024 to 16 MAY 2024