WAAS	APP CRS	Rwy Idg	5002
CH 93715	001°	TDZE	835
W36A		Apt Elev	845

RNAV (GPS) RWY 36

NORTH CENTRAL MISSOURI RGNL (MO8)

RNP APCH.

T NA For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using Kirksville altimeter setting. When local altimeter setting not received, use Kirksville altimeter setting and increase all LPV and LNAV/VNAV DA to 1169 feet and increase all visibility ⅛ mile; increase all MDA 100 feet, increase LNAV Cat C/D visibility ¼ mile, and Circling Cat C visibility ⅛ mile. Rwy 36 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct COROS and hold.

AWOS-2	KANSAS CITY CENTER	CTAF
118.425	125.25 235.975	122.9 L





CATEGORY	A	B	C	D
LPV DA	1085-1 250 (300-1)			
LNAV/VNAV DA	1085-1 250 (300-1)			
LNAV MDA	1300-1 465 (500-1)		1300-1⅜ 465 (500-1⅜)	
C CIRCLING	1300-1 455 (500-1)		1300-1½ 455 (500-1½)	1400-2 555 (600-2)

ELEV 845 TDZE 835

REIL Rwys 18 and 36 L

MIRL Rwy 18-36 L



NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024