

SE-1, 16 MAY 2024 to 13 JUN 2024

D-ATIS 135.1 CLNC DEL 126.05 CPDLC GND CON 121.9 348.6 NASHVILLE TOWER 118.6 257.8 NASHVILLE DEP CON 119.35 372.0	TOP ALTITUDE: 4000	TAKEOFF MINIMUMS: Rwys 2C, 2L, 2R, 13, 20L, 31: Standard with minimum climb of 500' per NM to 1100. Rwys 20C, 20R: Standard with minimum climb of 500' per NM to 1300.		NOTE: DME/DME/IRU or GPS required. NOTE: RNAV 1. NOTE: Radar required. NOTE: For Turbojet aircraft only. NOTE: Transponder code will be issued via PDC or Nashville clearance delivery. NOTE: If unable to accept climb rates, advise ATC on initial contact.	DEPARTURE ROUTE DESCRIPTION TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence... TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence... TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence... TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence... expect radar vectors to BGDDY, then on track 259° to DANLS. Maintain 4000. Expect clearance to filed altitude within five (5) minutes after departure.	SPKR TRANSITION (DANLS3.SPKR)
--	-----------------------------------	---	-------------	--	--	--

NOTE: Chart not to scale.

SE-1, 16 MAY 2024 to 13 JUN 2024