

WAAS CH 78101 W16A	APP CRS 160°	Rwy Idg TDZE Apt Elev	7000 682 682
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 16

DRAUGHON-MILLER CENTRAL TEXAS RGNL (TPL)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cats C/D visibility to ⅞ SM.

MALSR

MISSED APPROACH: Climb to 3600 direct FADXY and on track 074° to BARBA and hold, continue climb-in-hold to 3600.

AWOS-3PT
134.975

GRAY APP CON
120.075 370.0

CINC DEL
125.9

UNICOM
123.0 (CTAF) **0**

HOOD MOA

R-6302A

R-6302B

6000

3000

4 NM

160°

340°

(IF/IAF) IHSAZ

2400

160°

(6)

(FAF) IFDOH

2400

160°

CUMIX

1.7 NM to RW16

707

771

904±

3000 to IHSAZ

(20.5)

346°

CONRA

904±

FADXY

074°

(10)

BARBA

3000 to IHSAZ

(20.5)

311°

074°

254°

4 NM

MSA RW16 25 NM

3600

2541

2550

1181

901±

1001

ELEV 682

D

TDZE 682

160°

91

45

739

3

34

7000 X 100

4740 X 100

MIRL Rwy 3-21

MIRL Rwy 16-34 **0**

4 NM Holding Pattern

6000

3000

340°

160°

GP 3.00°

TCH 45

IHSAZ

IFDOH

2400

2400

1260

6 NM

3.6 NM

1 NM

0.7

3600

FADXY

tr 074°

BARBA

CUMIX

1.7 NM to RW16

0.7 NM to RW16

RW16

CATEGORY	A	B	C	D
LPV DA		882-½	200 (200-½)	
LNAV/VNAV DA		932-½	250 (300-½)	
LNAV MDA		960-½	278 (300-½)	
C CIRCLING	1140-1 458 (500-1)	1200-1 518 (600-1)	1280-1½ 598 (600-1½)	1420-2¼ 738 (800-2¼)

SC-3, 16 MAY 2024 to 13 JUN 2024

SC-3, 16 MAY 2024 to 13 JUN 2024

TEMPLE, TEXAS

Amdt 3 08SEP22

DRAUGHON-MILLER CENTRAL TEXAS RGNL (TPL)

31°09'N-97°24'W

RNAV (GPS) RWY 16