

WAAS CH 56313 W12A	APP CRS 124°	Rwy Idg 4999 TDZE 8 Apt Elev 9
--	------------------------	---


RNAV (GPS) RWY 12
HOUMA-TERREBONNE (HUM)

V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.


A When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting: increase LPV DA to 370 feet and all visibilities $\frac{1}{8}$ SM, increase LNAV/VNAV DA to 567 feet and all visibilities $\frac{1}{2}$ SM; increase all MDAs 80 feet and visibility Cals B, C and D $\frac{1}{4}$ SM. Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 1800 direct HOVPU and hold.

ATIS 120.25	NEW ORLEANS APP CON 118.9 350.35	HOUMA TOWER ★ 125.3 (CTAF) 0 346.3	GND CON 123.875	CLNC DEL 118.9 (When twr closed)	UNICOM 122.95
-----------------------	--	--	---------------------------	---	-------------------------



SC-4, 16 MAY 2024 to 13 JUN 2024



CATEGORY	A	B	C	D
LPV DA	293- $\frac{7}{8}$ 285 (300- $\frac{7}{8}$)			
LNAV/ VNAV DA	490-1 $\frac{3}{8}$ 482 (500-1 $\frac{3}{8}$)			
LNAV MDA	680-1 672 (700-1)		680-1 $\frac{7}{8}$ 672 (700-1 $\frac{7}{8}$)	
 CIRCLING	680-1 671 (700-1)		760-2 $\frac{1}{4}$ 751 (800-2 $\frac{1}{4}$)	760-2 $\frac{1}{2}$ 751 (800-2 $\frac{1}{2}$)

